



Gulper High Flow

- Up to 25 Litres per minute
- Specially designed to pump waste water
- Remote mounting Bilge Pump
- Non-choke valves
- Quiet running
- No filter required
- Self-priming up to 3 metres (9.8 ft)
- Will run dry and pump a mixture of air and water
- Easy to install in confined spaces
- Multi directional head
- Can be mounted almost anywhere
- Low power consumption
- Performance meets ISO15083 Small Craft Bilge Pump standard for vessels up to 12m (39.4 ft)

Gulper High Flow Bilge Pump	
Product code:	BP3552B (3554B)
Voltage:	12V (24V) D.C. Nominal
Recommended fuse size:	10 (5) Amps
Weight:	1.6Kg
Hose connections:	25.4mm (1")
Minimum wire size:	1.5mm ² (16 AWG)
Materials:	Glass filled nylon, acetal, EPDM, nitrile rubber, hypalon rubber, stainless steel, brass & aluminium
Materials in contact with fluid	Pump Body: Glass filled Nylon Inlet and Outlet Valves: Nitrile Rubber Diaphragm: Hypalon Rubber Screws: Stainless Steel Valve Housing: Acetal
Customisation	Rubber valve material may be changed, subject to volumes and applicable testing Diaphragms may be changed subject to volumes and testing to ensure suitable wear resistance

Maximum Head	3m (9.8ft)	
Maximum lift (self priming):	3m (9.8ft)	
Maximum head & lift:	4m (13.1ft)	
Dry running current:	5 Amps	2.5 Amps (24vdc)
Lift:	Head:	Flowrate / Current at 12vdc
1m (3ft)	0.4m (1.3 ft)	22 l/min / 6.2A
1m (3ft)	3.4m (11.1 ft)	15.5 l/min / 9.7A

